



Lieferprogramm - Ölfeldrohre (OCTG)

Außendurchmesser		Wanddicke in mm / inch																	
mm	inch	5,2 0,21	5,6 0,22	6,3 0,25	7,1 0,28	8 0,35	8,8 0,35	10 0,39	11 0,43	12,7 0,5	13 0,51	13,8 0,54	14,3 0,56	15 0,59	16,1 0,63	17,5 0,69	20,6 0,81	22,2 0,87	25,4 1
114,3	4 1/2																		
139,7	5 1/2																		
168,3	6 5/8																		
177,8	7																		
193,7	7 5/8																		
219,1	8 5/8																		
244,5	9 5/8																		
273,0	10 3/4																		
323,9	12 3/4																		
339,7	13 3/8																		
346,1	13 5/8																		
355,6	14																		
406,4	16																		
473,1	18 5/8																		
508,0	20																		
530,0	21																		
558,0	22																		
610,0	24																		

 Stahlgüten H40, J55, J55 UPG, K55

 Stahlgüten K55 FBN, N80Q, N80Q Schweißbar, L80, R95, P110 auf Anfrage

 Stahlgüten H40, J55, J55 UPG, K55, K55 FBN, N80Q, N80Q Schweißbar, L80, R95, P110

max. 18,5 mm (0,728") für K55

Max. Länge:

16m (53ft) bei P110, K55 FBN, L80, N80 Q, N80 Q Schweißbar, R95

18m (59ft) bei H40, J55, J55 Schweißbar, J55 UPG, K55

Hohe Kollapsbeständigkeit auf Anfrage